



SAFETY DATA SHEET

Synthetic Manual Transmission & Transaxle Gear Lubricant

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification	
Product identifier	
Product name	Synthetic Manual Transmission & Transaxle Gear Lubricant
Product number	MTG
Recommended use of the che	emical and restrictions on use
Application	Lubricating oil.
Uses advised against	Avoid the formation of mists.
Details of the supplier of the s	afety data sheet
Supplier	AMSOIL INC. Bordner, Ladner, Gervais Scotia Plaza, 40 King St W Toronto, ON, Canada M5H 3Y4 T: +1 416-367-6547
Manufacturer	AMSOIL INC. One AMSOIL Center, Superior, WI 54880, USA. T: +1 715-392-7101 compliance@amsoil.com
Emergency telephone number	
Emergency telephone	CHEMTREC: Within USA and Canada: 1-800-424-9300 Outside the USA and Canada: +1 703-741-5970 (collect calls accepted) 24/7
2. Hazard(s) identification	
Classification of the substance	e or mixture
OSHA/WHMIS Regulatory Status	This Product is not Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.
Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412
Label elements	
Hazard statements	H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P501 Dispose of contents/ container in accordance with national regulations.
Other hazards	

This product does not contain any substances classified as PBT or vPvB.



Synthetic Manual Transmission & Transaxle Gear Lubricant

3. Composition/information o	n ingredients
Vixtures	
Dec-1-ene, homopolymer, h oligomers, hydrogenated CAS number: 68037-01-4	ydrogenated Dec-1-ene, 25 - <50%
Classification Asp. Tox. 1 - H304	
(Z)-Octadec-9-enylamine	0.025 - <0.25%
CAS number: 112-90-3	
M factor (Acute) = 10	M factor (Chronic) = 10
Classification Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
p-Dodecylphenol CAS number: 104-43-8 M factor (Acute) = 10	0.025 - <0.25% M factor (Chronic) = 1
Classification Skin Corr. 1C - H314 Eye Dam. 1 - H318 Repr. 1B - H360 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
Ethanediol	<0.025%
CAS number: 107-21-1 Classification Acute Tox. 4 - H302 STOT RE 2 - H373	
The full text for all hazard sta	tements is displayed in Section 16.
Composition comments	The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.
I. First-aid measures	
Description of first aid measu	ires
General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medica personnel.

SAVE UP TO 25%

Synthetic Manual Transmission & Transaxle Gear Lubricant

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact	Rinse with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
Most important symptoms and	l effects, both acute and delayed
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Prolonged contact may cause dryness of the skin.
Eye contact	May cause temporary eye irritation.
Indication of immediate medic	al attention and special treatment needed
Notes for the doctor	Treat symptomatically.
Specific treatments	No special treatment required.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire- extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Special hazards arising from t	he substance or mixture
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Contains Hydrocarbons. The product is immiscible with water and will spread on the water surface.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak.

SAVE UP TO 25%

Synthetic Manual Transmission & Transaxle Gear Lubricant

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	
6. Accidental release measure	s	
Personal precautions, protectiv	ve equipment and emergency procedures	
Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Use protective equipment appropriate for surrounding materials.	
Environmental precautions		
Environmental precautions	Harmful to aquatic life with long lasting effects. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).	
Methods and material for containment and cleaning up		
Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of contents/container in accordance with national regulations.	
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.	
7. Handling and storage		
Precautions for safe handling		
Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid contact with used product. Do not reuse empty containers.	
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.	
Conditions for safe storage, in	cluding any incompatibilities	
Storage precautions	Store away from incompatible materials (see Section 10). Keep container tightly closed, in a cool, well ventilated place. Protect containers from damage.	
Storage class	Chemical storage.	
Specific end uses(s) Specific end use(s)	The identified uses for this product are detailed in Section 1.	
8. Exposure Controls/personal	protection	
Control parameters		

Occupational exposure limits

Synthetic Manual Transmission & Transaxle Gear Lubricant

Comments

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Under conditions which may generate mists, the following exposure limits are recommended: Long-term exposure limit (8-hour TWA): 5 mg/m³ Short-term exposure limit (15-minute): 10 mg/m³

Ethanediol

Ceiling exposure limit: ACGIH 100 mg/m³ Aerosol

A4

ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

controlsexposure to airborne contaminants.Eye/face protectionEyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. The following protection should be worn: Chemical splash goggles.Hand protectionChemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contaminated in specified by the glove and and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.Other skin and body rotectionAppropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contaminated work clothing should not be allowed out of the workplace. Wash contaminated	I	
eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. The following protection should be worn: Chemical splash goggles.Hand protectionChemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.Other skin and body rotectionAppropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contaminated work clothing should not be allowed out of the workplace. Wash contaminated dowing and using the toilet. When using do not eat, drink or smoke.Respiratory protectionRespiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.Chemical seposureRespiratory protection complying with an approved standard should be wor	Appropriate engineering controls	
a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at 	Eye/face protection	eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and
should be worn if a risk assessment indicates skin contamination is possible. Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn. Environmental exposure controls Keep container tightly sealed when not in use.	Hand protection	a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any
allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn. Environmental exposure controls Keep container tightly sealed when not in use.	Other skin and body protection	
assessment indicates inhalation of contaminants is possible. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn. Environmental exposure controls	Hygiene measures	allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When
controls	Respiratory protection	assessment indicates inhalation of contaminants is possible. Provide adequate ventilation.
9. Physical and Chemical Properties	Environmental exposure controls	Keep container tightly sealed when not in use.
	9. Physical and Chemical P	roperties

Information on basic physical and chemical properties Appearance Liquid. Option Vallant

Color	Yellow.
Odor	Mild hydrocarbon.
Odor threshold	Not available.



Synthetic Manual Transmission & Transaxle Gear Lubricant

рН	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	214°C Cleveland open cup. [ASTM D 92]
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.8468
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	87.6 cSt @ 40°C 13.9 cSt @ 100°C [ASTM D 445]
Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Fire point	236°C Cleveland open cup. [ASTM D 92]
Pour point	-54°C [ASTM D 97]
10. Stability and reactivity	
Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.
11. Toxicological information	
Information on toxicological ef	fects
Toxicological effects	Not regarded as a health hazard under current legislation.
Acute toxicity - oral	

Acute toxicity - oral



Synthetic Manual Transmission & Transaxle Gear Lubricant

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	54,421.77
Acute toxicity - dermal	
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	163,265.31
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (vapours mg/l)	1,632.65
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation	
Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitization	
Respiratory sensitization	Based on available data the classification criteria are not met.
Skin sensitization	
Skin sensitization	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
Reproductive toxicity	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity -	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
General information	No specific health hazards known. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin Contact	Prolonged contact may cause dryness of the skin.
Eye contact	May cause temporary eye irritation.

BUY ONLINE

FREE CATALOG

SAVE UP TO 25%

Synthetic Manual Transmission & Transaxle Gear Lubricant

Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.

Toxicological information on ingredients.

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated

Acute toxicity - oral	
Notes (oral LD₅₀)	LD₅₀ >5000 mg/kg, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.
Acute toxicity - dermal	
Notes (dermal LD₅₀)	LD₅₀ >2000 mg/kg, Dermal, Rat REACH dossier information. Based on available data the classification criteria are not met.
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	LC_{50} >5.2 mg/l, Inhalation, Rat REACH dossier information. Based on available dat the classification criteria are not met.
Skin corrosion/irritation	
Animal data	Dose: 0.5 mL, 24 hours, Rabbit Erythema/eschar score: No erythema (0). Edema score: No oedema (0). Primary dermal irritation index: 0.5 REACH dossier information. Based on available data the classification criteria are not met.
Serious eye damage/irritati	ion
Serious eye damage/irritation	Dose: 0.1 mL, 72 hours, Rabbit Not irritating. REACH dossier information. Based o available data the classification criteria are not met.
Skin sensitization	
Skin sensitization	Guinea pig maximization test (GPMT) - Guinea pig: Not sensitizing. REACH dossie information. Based on available data the classification criteria are not met.
Germ cell mutagenicity	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information. Based on availabl data the classification criteria are not met.
Reproductive toxicity	
Reproductive toxicity - fertility	One-generation study - NOAEL 1000 mg/kg/day, Oral, Rat P REACH dossier information. Based on available data the classification criteria are not met.
Aspiration hazard	
Aspiration hazard	Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
	may cause chemical pheumonius.

Toxicity

Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated

Synthetic Manual Transmission & Transaxle Gear Lubricant

Toxicity	Based on available data the classification criteria are not met. Aquatic toxicity is unlikely to occur.
Acute aquatic toxicity	
Acute toxicity - fish	LL₅₀, 96 hours: >1000 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EL₅₀, 48 hours: >1000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EL₅₀, 72 hours: >1000 mg/l, Selenastrum capricornutum
Acute toxicity - microorganisms	NOEC, 28 days: 2 mg/l, Activated sludge
Chronic aquatic toxicity	
Chronic toxicity - aquatic invertebrates	NOELR, 21 days: 125 mg/l, Daphnia magna
Persistence and degradability	
Persistence and degradability The d	egradability of the product is not known.
Ecological information on ingredients.	
Dec-1-e	ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated
Persistence and degradability	Not readily biodegradable.
Biodegradation	Water - Degradation 2%: 28 days
Bioaccumulative potential	
Bio-Accumulative Potential No da	ta available on bioaccumulation.
Partition coefficient Not av	vailable.
Ecological information on ingredients.	
Dec-1-	ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated
Partition coefficient	log Pow: >6.5
Mobility in soil	
Mobility No da	ta available.
Ecological information on ingredients.	
Dec-1-	ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated
Mobility	The product is insoluble in water.
Surface tension	27-29 mN/m @ 20°C
Other adverse effects	
	known.
13. Disposal considerations	
Waste treatment methods	

SAVE UP TO 25%

Synthetic Manual Transmission & Transaxle Gear Lubricant

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.
Disposal methods	Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.
14. Transport information	
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT, TDG).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

Transport labels

No transport warning sign required.

Packing group

Not applicable.

Environmental hazards

Environmentally Hazardous Substance No.

Special precautions for user

Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information	
Regulatory References	OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation
Regulatory References	(SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:



Synthetic Manual Transmission & Transaxle Gear Lubricant

Ethanediol

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated

1.0 %

Ethanediol 1.0 %

CAA Accidental Release Prevention None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins The following ingredients are listed or exempt:

Ethanediol Known to the State of California to cause developmental and reproductive toxicity.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

Ethanediol

California Air Toxics "Hot Spots" (A-II) None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

Ethanediol

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Ethanediol

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Ethanediol

Minnesota "Right To Know" List The following ingredients are listed or exempt:

Ethanediol

New Jersey "Right To Know" List The following ingredients are listed or exempt:



Synthetic Manual Transmission & Transaxle Gear Lubricant

Bis(2-ethylhexyl) hydrogen phosphate

Ethanediol

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Ethanediol

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Abbreviations and acronyms used in the safety data sheet	C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose,Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE= Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very Bioaccumulative.
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	This is the first issue.
Revision date	4/12/2018
SDS No.	7394

SAVE UP TO 25%

Synthetic Manual Transmission & Transaxle Gear Lubricant

Hazard statements in full	H302 Harmful if swallowed.
	H304 May be fatal if swallowed and enters airways.
	H314 Causes severe skin burns and eye damage.
	H318 Causes serious eye damage.
	H335 May cause respiratory irritation.
	H360 May damage fertility or the unborn child.
	H373 May cause damage to organs through prolonged or repeated exposure.
	H373 May cause damage to organs (Gastro-intestinal tract, liver, immune system) through
	prolonged or repeated exposure.
	H400 Very toxic to aquatic life.
	H402 Harmful to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.